



Olex a Nexans company
ABN 61 087 542 863
15/300 LaTrobe Street, Melbourne
Victoria, 3000, Australia

TELEPHONE *61 03 8739 3333
FACSIMILE *61 03 8739 3339
*1300 CABLES
www.olex.com.au

Customer :
Reference:

28 September 21

DESCRIPTION: One Core 240 mm² Flexible Multiple Stranded Plain Annealed Copper, 0.6/1 kV, PVC (V-90) (V-90) Insulated (2.2 mm min av wall), Multiple Stranded Conductor Cable to AS/NZS 5000.1.

Product Code : **BAAE90AA001** Ident No. : 1001,041240,01,0000
Colour Code:

Insulation : Green/Yellow or Yellow /Green - 2 or 3 extruded stripes /metre marked

Physical Properties:

Overall cable diameter: 25.4 mm nom +/- 1.3 mm
Main Core Dimensions - Conductor : 21.0 mm Insulation : 25.4 mm
Maximum Recommended Safe Pulling Tension : 4.83 kN
Minimum Recommended Bending Radius :
Pulling in : 229 mm
Set in Position : 152 mm

Electrical Properties:

Maximum conductor DC resistance = 0.0801 ohm/km @ 20°C
Minimum insulation resistance = 3.3 megohm.km @ 20°C

All Above Information is Subject to Change Without Notice

