



Olex a Nexans company  
ABN 61 087 542 863  
15/300 LaTrobe Street, Melbourne  
Victoria, 3000, Australia

TELEPHONE \*61 03 8739 3333  
FACSIMILE \*61 03 8739 3339  
\*1300 CABLES  
www.olex.com.au

Customer :  
Reference:

28 September 21

**DESCRIPTION:** One Core 400 mm<sup>2</sup> Flexible Multiple Stranded Plain Annealed Copper, 0.6/1 kV, PVC (V-90) (V-90) Insulated (2.6 mm min av wall), Multiple Stranded Conductor Cable, to AS/NZS 5000.1.

---

Product Code : **BAAE92AA001** Ident No. : 1001,041400,01,0000  
Colour Code:

Insulation : Green/Yellow or Yellow /Green - 2 or 3 extruded stripes /metre marked

Physical Properties:

Overall cable diameter: 32.0 mm nom +/- 1.6 mm  
Main Core Dimensions - Conductor : 26.8 mm Insulation : 32.0 mm  
Maximum Recommended Safe Pulling Tension : 7.91 kN  
Minimum Recommended Bending Radius :  
Pulling in : 288 mm  
Set in Position : 192 mm

Electrical Properties:

Maximum conductor DC resistance = 0.0486 ohm/km @ 20°C  
Minimum insulation resistance = 3.1 megohm.km @ 20°C

All Above Information is Subject to Change Without Notice

